




Video Surveillance C-MOR6RM+ Data Sheet

Chassis	
Application	Digital video surveillance for the use in networks or over internet for up to 6 network cameras C-MOR6RM+ version with upgrade function for up to 15 cameras Please note that additional cameras interact with the memory capacity and processor performance
Basic function	<ul style="list-style-type: none"> -Plug&Play installation -Permanent recording -Automatic motion detection -Recording time up to 360 days -IP configuration either over web interface or front display of device -Optimized hardware for 6 cameras, additional cameras maybe activated through online licensing -Support of the most IP cameras with JPEG/MJPEG standard -Support of many PTZ cameras -Time control of recordings configurable with time frame definition -Automatic FTP backup for archiving/data saving -Remote access -Support of mobile devices like smart phones and cell phones with video player -User interface in English and German -Usage of alternate IP technics like WLAN and ethernet over powerline
Advanced C-MOR-Functions	<ul style="list-style-type: none"> -E-mail or mobile alarm at camera failure, vandalism or error -E-mail or mobile alarm at motion detection for each camera configurable separately -Motion detection recordings forwarding in e-mails -Automatic FTP backup for archiving or data backup -Internet remote access without any additional software and without installation on the local Computer -Usage of free definable black white picture masks for motion detection areas -Integration of external switches for door alarm, motion detection, temperature monitoring etc. -Support of mobile devices like mobile phones, and handies with live pictures in pre-definable picture sizes with direct PTZ control -Possibility to upgrade up to 9 cameras
C-MOR Security-Functions	<ul style="list-style-type: none"> -User rights in 3 steps; administrator, common user and demo user rights -Encrypted internet access over SSL -SMTP authentication for save e-mail-delivery
Standards	IEEE 802.3 (10BaseT), IEEE 802.3u (100BaseTX), HTTP 1.1, HTTPS, FTP, MPEG1, MPEG4, JPEG, SMTP
Ports	2 x Ethernet 10/100/1000 Mbit RJ45
Certifications	CE, EN55022 Class A, EN55024, EN60950
Processor	Q6600, 2.4GHz, 2x4MB Cache, 1066MHz, FSB 1333MHz
Main Memory	1024MB
Hard Drive	750GB SATAII
Weight	28.7 lbs (ca. 13 kg)
Power Supply	315W, 100/240V, 50/60Hz, AC, internal
Dimensions (WxHxD)	23.6" (600mm) x 17.5" (444mm) x 1.7" (43,6mm)
Chassis	1HE 19"-Rack
Warranty	2 years